



Submersible Pumps for Industry and Sewerage

Tsurumi products are distributed worldwide and renowned for their advanced technological design. For professional use.



A | Tsurumi Stuffing Box - absolutely watertight



The stuffing box is located at the cable entry section and takes the part of sealing off water. As the cable conductors consist of twisted wires, water may penetrate into the motor by the capillary phenomenon when cable sheath or insulation is damaged or when the end of the cable is submerged. The construction is such that a certain part of the insulation of each conductor is peeled and filled with rubber or epoxy resin for the complete sealing.

B | Continuous use under dry-run

Located directly above the motor windings, a snap-action self-resetting bi-metal device cuts off voltage from all three phase windings simultaneously if the current is too large in one, two or all three windings, or if the windings get too hot.

Tsurumi enables measurement of winding resistance and insulation from the far end of the cable, without ever removing the cover from the motor in the field.


C | Ball bearings of highest quality

Due to the high quality of the shaft and the bear rings all pumps can be run horizontally when entirely submerged.

D | Double mechanical SiC seal in oil bath



All Tsurumi pumps dispose of a double mechanical seal for increased durability:

The double inside mechanical seals of all our sewage pumps have sealing rings of Silicon Carbide, no other material has greater hardness. Resistance to temperature fluctuation and corrosion is also the best available.



E | Oil Lifter

A special patented guide vane is attached inside the oil chamber. With the motor rotation oil is pumped up. Therefore even at low oil level lubrication and cooling of the mechanical seal is secured.



F | Impeller

A variety of types are available, depending on applications, i.e. open type, closed type, non-clog type and vortex type.

Type	Model	Bore mm	Power output kW	Poles	Impeller	Motor protector (built-in)	Level sensor	Guide rail fitting	Page
Sewage	POMA	50	0,15	2	Vortex	●	●		4
	OM(A)	32	0,15	2	Vortex	●	●		4
	PU	50 80	0,25 - 1,5	2	Vortex	●	●	●	5
Salt Water	TM	50	0,4 0,75	2	Vortex	●			6
Sewage	U	40 - 80	0,25 - 3,7	2	Vortex	●	●	●	7
	UZ	50 - 100	1,5 - 11	4	Vortex	●		●	8
	B	50 - 100	0,4 - 7,5	2 4	Canal	●		●	9
	C	50 - 100	0,75 - 11	2 4	Canal Cutter mechanism	●		●	10
	BZ	80 100	1,5 - 11	4	Canal	●		●	11
Decanting	FHP	50	0,4 0,75	2	Canal	●			12
Scum Collection	FSP	50	0,4 0,75	2	Canal	●			12
Corrosion Resistant	SFQ	50 80	0,4 - 11	2	Vortex	●		●	13
	SQ	40 50	0,25 - 0,75	2	Vortex	●			14
Flame Proof	BX	80 100	1,6 - 3,8	2 4	Canal	●		●	15
	CX	80 100	1,6 - 3,8	2 4	Canal Cutter mechanism	●		●	16
	UX	50 80	1,6 - 4,0	2	Vortex	●		●	17
Aeration	TRN		0,75 - 40	2 4	Vortex	●			18
	BER		0,75 - 5,5	2 4	Canal	●		●	19



Non-clog impeller

An impeller used in centrifugal pumps. This impeller is characteristic for preventing internal clogging by solids in the pumped liquid.



Non-clog impeller (shrouded type)

An impeller having a wide channel extending from inlet to exit, which prevents internal clogging by solids sucked in via the inlet.



Non-clog impeller (with cutter mechanism)

A "cutter mechanism" is provided by the combined action of a carbide blade integrated into a non-clog impeller and the saw-shaped inner surface of a suction cover.



Non-clog impeller BZ-series

Non-clog impeller allows large diameter of foreign matter with respect to discharge bore.



Vortex impeller (open type)

The semi-open impeller blade rotates about 0,5mm above the wear plate, clearing themselves of possible settled matter.



Vortex impeller

This impeller is used mainly to avoid clogging or wear by large or stringy solids in the water. It accelerates part of the water to great speed, and this speed is used to smoothly move all the water from inlet to outlet.



Vortex impeller



Model	Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg w/o cable	Impeller passage mm
POMA	●	1	50	0,15	1	2850	5,7	190 condensor	6,6	35


Pump casing, head cover and impeller made of fibre-reinforced plastic (FRP). 35mm impeller passage.

Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Domestic sewage
Pump	Compo-nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Glass fibre reinforced plastic
		Upper casing	Glass fibre reinforced plastic
		Lower casing	Plastic
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz
	Material	Casing	Stainless steel EN-X5CrNi18-10
		Shaft	Stainless steel EN-X6Cr13
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, flange



W1: continuous running water level



POMA 1-phase 50Hz



Model	Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg w/o cable	Impeller passage mm
OM	●	1	32	0,15	1	2850	7,5	195 condensor	5,9	10


Pump casing, head cover and impeller made of fibre-reinforced plastic (FRP). Model OMA with level control.

Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Domestic sewage
Pump	Compo-nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Glass fibre reinforced plastic
		Upper casing	Glass fibre reinforced plastic
		Lower casing	Glass fibre reinforced plastic
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz
	Material	Casing	Stainless steel EN-X5CrNi18-10
		Shaft	Stainless steel EN-X6Cr13
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, flange



W1: continuous running water level

OM(A) 1-phase 50Hz






Specifications:

	Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
	free standing	with guide rail fitting									free standing	with guide rail fitting	
manual	50PU2.25	optional	1	50	0,25	3	2850	6,6	210	direct	6,1	-	35
	50PU2.4	optional	2	50	0,4	3	2850	9,6	270	direct	7,0	-	35
	50PU2.4S	optional		50	0,4	1	2850	9,6	270	condensor	7,1	-	35
	50PU2.75	optional	3	50	0,75	3	2850	12,5	360	direct	8,3	-	35
	50PU2.75S	optional		50	0,75	1	2850	12,5	360	condensor	8,9	-	35
	80PU21.5	optional	4	80	1,5	3	2850	16,0	800	direct	15,8	-	46
autom.	50PUA2.4	optional		50	0,4	3	2850	9,6	270	direct	7,5	-	35
	50PUA2.4S	optional		50	0,4	1	2850	9,6	270	condensor	7,7	-	35
	50PUA2.75	optional		50	0,75	3	2850	12,5	360	direct	8,9	-	35
	50PUA2.75S	optional		50	0,75	1	2850	12,5	360	condensor	9,5	-	35





Light and solid - Guide rail fitting available for all models.

ø Discharge bore mm			50mm,80mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage, water with solids
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Glass fibre reinforced plastic
		Upper casing	Glass fibre reinforced plastic
		Lower casing	Plastic
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz
	Material	Casing	Stainless steel EN-X5CrNi18-10
		Shaft	Stainless steel EN-X5CrNi18-10
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, flange
Optional Accessories			Guide rail fitting "TOK" for small pumps




Dimensions in mm:

Model	A	A1	A2	B	D	D1	D2	FL1	FL2	H	W1	W2
50PU2.25	236	115	81	102	162	76	86	-	-	349	110	310
50PU2.4	236	115	81	102	162	76	86	-	-	360	110	325
50PU2.4S	236	115	81	102	162	76	86	-	-	360	110	325
50PU2.75	236	115	81	102	162	76	86	-	-	374	110	335
50PU2.75S	236	115	81	102	162	76	86	-	-	374	110	335
80PU21.5	295	145	99	130	196	92	104	-	-	475	150	427
50PUA2.4	236	115	81	102	173	76	97	115	607	374	-	-
50PUA2.4S	236	115	81	102	173	76	97	115	607	374	-	-
50PUA2.75	236	115	81	102	173	76	97	115	621	388	-	-
50PUA2.75S	236	115	81	102	173	76	97	115	621	388	-	-



50PU2.25
50PU2.4S
50PU2.4
50PU2.75
80PU21.5
50PU2.75S



50PUA2.4S
50PUA2.4
50PUA2.75
50PUA2.75S

W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately




Specifications:

Model	Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable	Impeller passage mm
50TM2.4S	1	50	0,4	1	2850	12,0	290	condensor	6,7	10
50TM2.75	2	50	0,75	3	2850	15,0	350	direct	7,8	10

All parts in contact with the medium are made of titanium. Titanium has a far stronger oxide film on its surface than stainless steel does. This prevents the pump from being corroded in the seawater which has a very high chlorine ion concentration.




ø Discharge bore mm			50mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Saltwater, Seawater
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Glass fibre reinforced plastic
		Upper casing	Glass fibre reinforced plastic
		Lower casing	Glass fibre reinforced plastic
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG15)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz, 3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Titanium
		Shaft	Titanium
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, flange



Dimensions in mm:

Model	A	A1	A2	B	B1	D	D1	D2	H	W1
50TM2.4S	236	115	81	102	90	162	76	86	360	110
50TM2.75	236	115	81	102	90	162	76	86	374	110



W1: continuous running water level




Specifications:

	Model		Colour code curve		Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
	free standing	with guide rail fitting										free standing	with guide rail fitting	
manual	40U2.25	optional		1	40	0,25	3	2850	7,4	264	direct	13,5	-	35
	40U2.25S	optional			40	0,25	1	2850	7,4	264	split-phase	14,0	-	35
	50U2.4	optional		2	50	0,4	3	2850	11,0	270	direct	19,2	-	35
	50U2.4S	optional			50	0,4	1	2850	11,0	270	condensor	20,0	-	35
	50U2.75	optional		3	50	0,75	3	2850	15,0	270	direct	23,0	-	35
	80U2.75	TOS80U2.75		4	80	0,75	3	2850	12,2	450	direct	29,0	24,0	46
	80U21.5	TOS80U21.5		5	80	1,5	3	2850	16,5	600	direct	40,0	36,0	46
	80U22.2	TOS80U22.2		6	80	2,2	3	2850	19,0	800	direct	55,0	51,0	56
autom.	80U23.7	TOS80U23.7		7	80	3,7	3	2850	23,5	1030	direct	62,0	58,0	56
	40UA2.25	optional			40	0,25	3	2850	7,4	264	direct	14,5	-	35
	40UA2.25S	optional			40	0,25	1	2850	7,4	264	split-phase	14,5	-	35
	50UA2.4	optional			50	0,4	3	2850	11,0	270	direct	20,0	-	35
	50UA2.4S	optional			50	0,4	1	2850	11,0	270	condensor	21,0	-	35
	50UA2.75	optional			50	0,75	3	2850	15,0	270	direct	24,0	-	35




Vortex impeller with wide pump casing, preventing clogging by solids and fibrous matter.

ø Discharge bore mm			40mm,50mm,80mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage, water with solids
Pump	Components	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E,Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz,3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-150
		Shaft	Stainless steel EN-X6Cr13,Stainless steel EN-X30Cr13
		Cable	Rubber, 10m H07RN-F
Discharge Connection			Inside thread, JIS10K flange
Optional Accessories			Guide rail fitting "TOK" for small pumps,Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types



Dimensions in mm:

Model	A	A4	B	D	FL1	FL2	H	W1	W2
40U2.25	241	207	107	172	-	-	383	100	340
40U2.25S	241	207	107	172	-	-	383	100	340
50U2.4	236	199	102	158	-	-	400	105	355
50U2.4S	236	199	102	158	-	-	433	105	390
50U2.75	249	212	102	172	-	-	395	105	365
80U2.75	383	329	173	172	-	-	421	130	385
80U21.5	420	366	173	200	-	-	501	135	430
80U22.2	502	410	225	240	-	-	562	160	490
80U23.7	502	410	226	234	-	-	565	160	520
40UA2.25	241	207	107	194	100	585	433	-	-
40UA2.25S	241	207	107	194	100	585	433	-	-
50UA2.4	236	199	102	187	105	590	450	-	-
50UA2.4S	236	199	102	187	105	590	450	-	-
50UA2.75	383	246	102	172	105	590	475	-	-



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately





Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
50UZ41.5	TOS50UZ41.5	1	50	1,5	3	1450	10,2	644	direct	52,0	50,0	50
80UZ41.5	TOS80UZ41.5	2	80	1,5	3	1450	7,5	1120	direct	66,0	56,0	80
80UZ42.2	TOS80UZ42.2	3	80	2,2	3	1450	8,8	1395	direct	66,0	57,0	80
80UZ43.7	TOS80UZ43.7	4	80	3,7	3	1450	12,7	1520	direct	72,0	63,0	80
100UZ43.7	TOS100UZ43.7	5	100	3,7	3	1450	10,1	1890	direct	79,0	70,0	100
80UZ45.5	TOS80UZ45.5	6	80	5,5	3	1450	15,0	1900	direct	129,0	125,0	80
100UZ45.5	TOS100UZ45.5	7	100	5,5	3	1450	13,2	2360	direct	145,0	134,0	100
80UZ47.5	TOS80UZ47.5	8	80	7,5	3	1450	19,0	1900	direct	142,0	137,0	80
100UZ47.5	TOS100UZ47.5	9	100	7,5	3	1450	15,6	2500	direct	158,0	147,0	100
80UZ411	TOS80UZ411	10	80	11	3	1450	22,8	1800	star/delta	178,0	176,0	80
100UZ411	TOS100UZ411	11	100	11	3	1450	19,0	2600	star/delta	191,0	180,0	100




Vortex impeller with wide pump casing, 4-pole motor, no clogging.

ø Discharge bore mm			50mm,80mm,100mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage, water with solids
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E,Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.,3-phase / 400V / 50Hz / s.d.
	Material	Casing	Grey iron casting EN-GJL-150,Grey iron casting EN-GJL-200
Shaft		Stainless steel EN-X30Cr13	
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, JIS10K flange
Optional Accessories			Guide rail fitting "TOS" (guide support, duck foot bend, lift stand set for free standing types



Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
50UZ41.5	405	228	123	142	179	250	110	140	566	170	525
80UZ41.5	531	312	126	200	285	261	128	133	637	240	595
80UZ42.2	531	312	126	200	285	261	128	133	637	240	595
80UZ43.7	557	312	153	200	285	291	141	150	688	240	645
100UZ43.7	628	368	155	240	330	314	149	165	737	290	695
80UZ45.5	595	342	160	230	290	358	179	179	899	280	770
100UZ45.5	652	387	160	260	335	358	179	179	939	320	810
80UZ47.5	595	342	160	230	290	358	179	179	920	280	790
100UZ47.5	652	387	160	260	335	358	179	179	960	320	830
80UZ411	602	342	168	230	292	358	179	179	981	295	825
100UZ411	660	387	168	230	337	358	179	179	1021	335	865



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately





Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
50B2.4	TOS50B2.4	1	50	0,4	3	2850	9,0	260	direct	23,0	22,0	19
50B2.75	TOS50B2.75	2	50	0,75	3	2850	12,0	435	direct	25,0	24,0	20
50B2.75H	TOS50B2.75H	3	50	0,75	3	2850	15,2	360	direct	24,0	23,0	20
80B21.5	TOS80B21.5	4	80	1,5	3	2850	16,8	1000	direct	36,0	34,0	40
100B42.2	TOS100B42.2	5	100	2,2	3	1450	16,0	1500	direct	70,0	64,0	45
100B43.7	TOS100B43.7	6	100	3,7	3	1450	16,4	2000	direct	86,0	80,0	53
100B43.7H	TOS100B43.7H	7	100	3,7	3	1450	20,0	1180	direct	84,0	78,0	35
100B45.5	TOS100B45.5	8	100	5,5	3	1450	26,0	2080	direct	147,0	140,0	40
100B47.5	TOS100B47.5	9	100	7,5	3	1450	29,7	2260	direct	169,0	150,0	40




Proprietary impeller and shaver mechanism (special groove) ensures that waste water and sewage are efficiently transferred.

ø Discharge bore mm			50mm,80mm,100mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage
Pump	Compo- nents	Impeller	Non-clog impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Ductile iron casting EN-GJS-450-10,Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E,Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-150,Grey iron casting EN-GJL-200
Shaft		Stainless steel EN-X6Cr13,Stainless steel EN-X30Cr13	
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, JIS10K flange
Optional Accessories			Guide rail fitting "TOS" (guide support, duck foot bend, lifting ch stand set for free standing types



Dimensions in mm:

Model	A	A1	A2	A3	B	B1	D	D1	D2	H	W1	W2
50B2.4	347	208	85	120	181	140	224	112	112	443	140	340
50B2.75	405	226	125	138	199	140	250	125	125	439	170	410
50B2.75H	405	226	125	138	199	140	250	125	125	415	145	385
80B21.5	446	267	125	165	234	140	250	125	125	536	190	465
100B42.2	569	322	154	210	303	-	331	164	167	616	225	570
100B43.7	575	322	160	210	308	-	339	164	175	690	235	645
100B43.7H	569	322	154	210	303	-	331	164	167	666	225	620
100B45.5	687	388	194	260	372	-	400	197	203	824	335	700
100B47.5	687	388	194	260	372	-	400	197	203	814	335	720



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately

Canal impeller with cutter mechanism



C 400V
50Hz



Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
50C2.75	TOS50C2.75	1	50	0,75	3	2850	11,5	335	direct	24,0	23,0	21
80C21.5	TOS80C21.5	2	80	1,5	3	2850	13,2	810	direct	36,0	34,0	37
100C42.2	TOS100C42.2	3	100	2,2	3	1450	13,5	1100	direct	70,0	64,0	44
100C43.7	TOS100C43.7	4	100	3,7	3	1450	16,0	1700	direct	86,0	80,0	60
100C45.5	TOS100C45.5	5	100	5,5	3	1450	18,1	2290	direct	140,0	133,0	40
100C47.5	TOS100C47.5	6	100	7,5	3	1450	23,0	2500	direct	159,0	152,0	40
100C411	TOS100C411	7	100	11	3	1450	26,0	2750	star/delta	184,0	177,0	50

Saw-shaped fixed blades are used in combination with carbide blades in an impeller-integrated structure. This construction ensures that fibrous matter is cut up, and sewage is transferred without clogging.




ø Discharge bore mm		50mm,80mm,100mm	
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Wastewater and liquid carrying waste and foreign matters
Pump	Compo-nents	Impeller	Non-clog impeller with cutter mechanism
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200 with sintered tungsten carbide alloy tip
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Ductile iron casting EN-GJS-700-2
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E,Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.,3-phase / 400V / 50Hz / s.d.
	Material	Casing	Grey iron casting EN-GJL-150,Grey iron casting EN-GJL-200
		Shaft	Stainless steel EN-X6Cr13,Stainless steel EN-X30Cr13
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Inside thread, JIS10K flange
Optional Accessories			Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) stand set for free standing types



Dimensions in mm:

Model	A	A4	B	D	H	W1	W2
50C2.75	405	351	196	250	415	145	385
80C21.5	446	392	234	250	536	190	465
100C42.2	594	489	328	324	616	225	570
100C43.7	602	497	333	331	680	235	635
100C45.5	687	582	372	400	824	335	700
100C47.5	687	582	372	400	814	335	720
100C411	710	605	372	431	1000	300	840



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately





Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
80BZ41.5	TOS80BZ41.5	1	80	1,5	3	1450	9,1	1480	direct	78,0	74,0	80
100BZ42.2	TOS100BZ42.2	2	100	2,2	3	1450	11,3	1800	direct	80,0	74,0	80
100BZ43.7	TOS100BZ43.7	3	100	3,7	3	1450	15,8	2220	direct	100,0	94,0	80
100BZ45.5	TOS100BZ45.5	4	100	5,5	3	1450	18,0	2630	direct	175,0	168,0	80
100BZ47.5	TOS100BZ47.5	5	100	7,5	3	1450	23,0	2960	direct	194,0	187,0	80
100BZ411	TOS100BZ411	6	100	11	3	1450	26,0	3570	star/delta	219,0	212,0	80
100BZ411H	TOS100BZ411H	7	100	11	3	1450	30,0	2810	star/delta	219,0	212,0	80





Non-clog impeller allows large diameter of foreign matter with respect to discharge bore. This ensures that waste water and sewage are efficiently transferred.

ø Discharge bore mm			80mm, 100mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage
Pump	Compo- nents	Impeller	Non-clog impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
	Motor	Type, Poles	
Lubrication		Turbine oil (ISO VG32)	
Insulation		Insulation class F	
Motor Protector (built-in)		Circle thermal cut-out	
Phase / Voltage		3-phase / 400V / 50Hz / d.o.l., 3-phase / 400V / 50Hz / s.d.	
Material		Casing	Grey iron casting EN-GJL-150
		Shaft	Stainless steel EN-X30Cr13
		Cable	Rubber, 10m H07RN-F
Discharge Connection			Inside thread, JIS10K flange
Optional Accessories			Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types



Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
80BZ41.5	523	302	129	190	303	273	133	140	631	235	590
100BZ42.2	551	317	129	190	328	273	133	140	631	235	590
100BZ43.7	584	327	153	200	328	289	139	150	681	235	640
100BZ45.5	716	407	204	280	380	421	205	216	925	305	790
100BZ47.5	716	407	204	280	380	421	205	216	946	305	820
100BZ411	727	407	215	280	377	431	205	226	1023	330	865
100BZ411H	727	407	215	280	377	431	205	226	1023	330	865



W1: continuous running water level


Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately

Canal impeller



Model	Colour code curve		Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg w/o cable	Dimensions in mm	
											A	B
FHP-4	●	1	50	0,4	1	2850	10,0	280	condensor	29,0	800	50
FHP-4T			50	0,4	3	2850	10,0	280	direct	27,0	765	50
FHP-8T	●	2	50	0,75	3	2850	13,0	420	direct	28,0	819	50


Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Treated sewage
Pump	Compo- nents	Impeller	Non-clog impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
		Float	Glass fibre reinforced plastic
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz, 3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-150
		Shaft	Stainless steel EN-X6Cr13
Cable		Rubber, 10m H07RN-F	
Discharge Connection			Hose coupling



FHP 400V
50Hz




Decanting pump - The special construction of the pump ensures that only supernatant water is discharged without any entrapment of sediments.



Model	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg w/o cable	Impeller passage mm
4-FSP	50	0,4	3	2850	4,9	180	direct	36,0	16
8-FSP	50	0,75	3	2850	5,3	255	direct	38,0	22



Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Treated sewage
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Upper casing	Grey iron casting EN-GJL-200
		Lower casing	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
		Float	Plastic
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-150
		Shaft	Stainless steel EN-X6Cr13
		Cable	Rubber, 10m H07RN-F
Discharge Connection			Hose coupling



FSP 400V
50Hz



Scum skimmer - The submersible scum skimmer FSP incorporates a jet injector (suction mechanism) for collecting scum efficiently.






Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
50SFQ2.4	-	1	50	0,4	3	2850	11,1	290	direct	20,0	-	6
50SFQ2.75	-	2	50	0,75	3	2850	14,2	430	direct	20,0	-	6
80SFQ21.5	-	3	80	1,5	3	2850	20,9	645	direct	36,0	-	6
80SFQ23.7	-	4	80	3,7	3	2850	24,6	1180	direct	52,0	-	15
80SFQ25.5	TOS80SFQ25.5	5	80	5,5	3	2850	30,0	1350	direct	124,0	113,0	30
80SFQ27.5	TOS80SFQ27.5	6	80	7,5	3	2850	34,8	2000	direct	123,0	112,0	30
80SFQ211	TOS80SFQ211	7	80	11	3	2850	44,0	1940	star/delta	143,0	132,0	30

Stainless steel pump - The SFQ pump has been developed exclusively for corrosive liquids. Applying austenitic steel in all wetted parts, the SFQ pump is a highly specialised pump in terms of design and materials.




Discharge bore mm		50mm,80mm	
Pumping Fluid	Temperature	0-40°C	
	Type of Fluid	Aggressive sewage	
Pump	Components	Impeller	Open type impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Stainless steel casting DIN GX5CrNiMo19-11-2
		Casing	Stainless steel casting DIN GX5CrNiMo19-11-2
		Suction Plate	Stainless steel casting DIN GX5CrNiMo19-11-2
Motor	Type, Poles	Shaft Seal	Silicon carbide in oil bath
		Impeller	Stainless steel casting DIN GX5CrNiMo19-11-2
		Casing	Stainless steel casting DIN GX5CrNiMo19-11-2
	Lubrication	Shaft	Stainless steel EN-X5CrNiMo17-12-2
		Cable	Rubber, 10m H07RN-F
		Discharge Connection	Inside thread, JIS10K flange



Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
50SFQ2.4	252	120	98	-	108	196	98	98	397	90	355
50SFQ2.75	252	120	98	-	108	196	98	98	397	90	355
80SFQ21.5	329	165	110	-	109	221	110	111	484	95	415
80SFQ23.7	359	180	125	-	154	257	125	132	552	130	500
80SFQ25.5	635	362	180	250	287	360	180	180	844	190	690
80SFQ27.5	635	362	180	250	287	360	180	180	844	190	690
80SFQ211	635	362	180	250	287	360	180	180	892	190	710



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately




Specifications:

Model	Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable	Impeller passage mm
40SQ2.25	1	40	0,25	3	2850	7,5	200	direct	12,0	6
40SQ2.25S		40	0,25	1	2850	7,5	200	condensor	12,5	6
50SQ2.4	2	50	0,4	3	2850	10,5	240	direct	12,0	6
50SQ2.4S		50	0,4	1	2850	10,5	240	condensor	12,5	6
50SQ2.75	3	50	0,75	3	2850	14,5	300	direct	14,0	6

Stainless steel pump - This compact submersible pump is for use with slightly corrosive liquids and uses harmless liquid paraffin as its lubrication oil.




ø Discharge bore mm			40mm,50mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Aggressive fluids, food industry
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	SCS13 (DIN GX5CrNi19-10)
		Casing	SCS13 (DIN GX5CrNi19-10)
		Suction Plate	Stainless steel EN-X5CrNi18-10
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles
	Lubrication		Turbine oil (ISO VG15)
	Insulation		Insulation class E
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		Single phase 230V / 110V / 50Hz,3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Stainless steel EN-X5CrNi18-10
		Shaft	Stainless steel EN-X5CrNi18-10
		Cable	Rubber, 10m H07RN-F
Discharge Connection			Hose coupling



Dimensions in mm:

Model	A	A1	B	H	W1
40SQ2.25	180	125	364	262	60
40SQ2.25S	180	125	364	262	60
50SQ2.4	180	125	364	262	60
50SQ2.4S	180	125	364	262	60
50SQ2.75	180	125	384	282	60



W1: continuous running water level



Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
80BX21.6	TOS80BX21.6	1	80	1,6	3	2850	16,8	1000	direct	52,0	50,0	49x41
100BX42.3	TOS100BX42.3	2	100	2,3	3	1450	16,0	1500	direct	79,0	73,0	47x53
100BX43.8	TOS100BX43.8	3	100	3,8	3	1450	16,4	2000	direct	93,0	87,0	81x53
100BX43.8H	TOS100BX43.8H	4	100	3,8	3	1450	20,0	1180	direct	92,0	86,0	35x62





Flame proof according to ATEX

An impeller having a wide channel extending from inlet to exit, which prevents internal clogging by solids sucked in via the inlet.



ATEX II 2G Ex d IIB

ø Discharge bore mm		80mm, 100mm	
Pumping Fluid	Temperature	0-40°C	
	Type of Fluid	Municipal sewage	
Pump	Components	Impeller	Non-clog impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles, Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-200
		Shaft	Stainless steel EN-X30Cr13
Cable		Rubber, 10m H07RN6G	
Discharge Connection		Inside thread, JIS10K flange	
Optional Accessories		Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types	



W1: continuous running water level

Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
80BX21.6	446	267	125	165	234	250	125	125	695	265	560
100BX42.3	597	337	154	210	328	324	158	166	761	340	625
100BX43.8	602	337	159	210	334	333	158	175	838	355	700
100BX43.8H	604	337	161	210	328	344	169	175	814	345	680

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately

Canal impeller with cutter mechanism



CX 400V
50Hz

Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
80CX21.6	TOS80CX21.6	1	80	1,6	3	2850	13,2	810	direct	52,0	50,0	43x60
100CX42.3	TOS100CX42.3	2	100	2,3	3	1450	13,5	1100	direct	78,0	72,0	67x56
100CX43.8	TOS100CX43.8	3	100	3,8	3	1450	16,0	1700	direct	94,0	88,0	70x81



Flame proof according to ATEX

A "cutter mechanism" is provided by the combined action of a carbide blade integrated into a non-clog impeller and the saw-shaped inner surface of a suction cover.




ATEX II 2G Ex d IIB

ø Discharge bore mm		80mm,100mm	
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Wastewater and liquid carrying waste and foreign matters
Pump	Compo- nents	Impeller	Non-clog impeller with cutter mechanism
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200 with sintered tungsten carbide alloy tip
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Ductile iron casting EN-GJS-700-2
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-200
		Shaft	Stainless steel EN-X30Cr13
		Cable	Rubber, 10m H07RN6G
Discharge Connection		Inside thread, JIS10K flange	
Optional Accessories		Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types	



Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
80CX21.6	446	267	125	165	234	250	125	125	695	265	560
100CX42.3	597	337	154	210	328	324	158	166	761	340	625
100CX43.8	602	337	159	210	334	333	158	175	838	355	700



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately



Specifications:

Model		Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
free standing	with guide rail fitting									free standing	with guide rail fitting	
50UX21.6	TOS50UX21.6	1	50	1,6	3	2850	18,4	330	direct	41,0	39,0	35
80UX21.6	TOS80UX21.6	2	80	1,6	3	2850	14,5	600	direct	48,0	44,0	46
80UX22.4	TOS80UX22.4	3	80	2,4	3	2850	16,0	800	direct	62,0	58,0	56
80UX24.0	TOS80UX24.0	4	80	4,0	3	2850	23,5	1030	direct	71,0	67,0	56


Flame proof according to ATEX

Featuring a vortex impeller recessed in the widely opened pump casing interior, the UX pump can handle sewage with large solids without clogging or winding.




ATEX II 2G Ex d IIB

ø Discharge bore mm		50mm,80mm	
Pumping Fluid	Temperature	0-40°C	
	Type of Fluid	Municipal sewage, water with solids	
Pump	Components	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Casing	Grey iron casting EN-GJL-200
		Impeller	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-200
		Shaft	Stainless steel EN-X30Cr13
		Cable	Rubber, 10m H07RN6G
Discharge Connection		Inside thread, JIS10K flange	
Optional Accessories		Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types	



Dimensions in mm:

Model	A	A1	A2	A3	B	D	D1	D2	H	W1	W2
50UX21.6	297	147	114	-	101	225	112,5	112,5	625	180	490
80UX21.6	420	252	114	150	173	225	112,5	112,5	658	210	520
80UX22.4	502	287	123	175	225	238	112,5	112,5	694	275	560
80UX24.0	502	287	123	175	225	238	112,5	112,5	742	275	605



W1: continuous running water level

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately

Specifications:


Diameter air pipe mm	Model	Colour code curve	Power output kW	Phases	r.p.m.	Starting method	Dry weight kg without cable	Cable m
32	32TRN2.75	1	0,75	3	2850	direct	55,0	10
32	32TRN21.5	2	1,5	3	2850	direct	55,0	10
50	50TRN42.2	3	2,2	3	1450	direct	140,0	10
50	50TRN43.7	4	3,7	3	1450	direct	150,0	10
50	50TRN45.5	5	5,5	3	1450	direct	170,0	10
80	80TRN47.5	6	7,5	3	1450	direct	190,0	10
80	80TRN412	7	12	3	1450	star/delta	200,0	10
80	80TRN417	8	17	3	1450	star/delta	220,0	20
100	100TRN424	9	24	3	1450	star/delta	460,0	20
150	150TRN440	10	40	3	1450	star/delta	635,0	20




**Submersible Aerators - self priming
- low maintenance - easy
installation**

ø Air inlet			32mm,50mm,80mm,100mm,150mm
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage, sewage of food industry
Pump	Compo- nents	Impeller	Vortex impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Stainless steel DIN-GX12Cr14
		Suction Plate	Stainless steel DIN-GX12Cr14
		Guide vane	Grey iron casting EN-GJL-200
		Air inlet	Grey iron casting EN-GJL-200
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.,3-phase / 400V / 50Hz / s.d.
	Material	Casing	Grey iron casting EN-GJL-150,Grey iron casting EN-GJL-200
		Shaft	Stainless steel EN-X30Cr13,Stainless steel EN-X20Cr13
Cable		Rubber, H07RN-F	
Air pipe connection			Inside thread, flange

Air Emission Volume - Water Depth Curve
(Air Emission Volume at 20°C)





Air Emission Volume - Water Depth Curve
(Air Emission Volume at 20°C)



Dimensions in mm:

Model	A	A1	B	D	D1	H	W1	SA	SB	SC	SD
32TRN2.75	371	184	146	420	90	473	81	180	116	175	-
32TRN21.5	371	184	146	420	90	473	81	180	116	275	-
50TRN42.2	660	271	226	700	140	689	123	230	154	370	-
50TRN43.7	660	271	226	700	140	694	123	230	154	370	-
50TRN45.5	660	271	226	700	140	835	123	230	154	370	-
80TRN47.5	660	271	246	700	140	868	133	245	180	-	585
80TRN412	660	271	246	700	140	898	133	245	180	-	585
80TRN417	660	271	246	700	140	958	133	245	180	-	585
100TRN424	980	385	417	1000	230	1254	272	345	256	-	760
150TRN440	980	410	452	1050	280	1407	269	448	370	740	863





Specifications:

Diameter air pipe mm	Model		Colour code curve	Power output kW	Phases	r.p.m.	Starting method	tank dimensions			Dry weight kg without cable	
	free standing	with guide rail fitting						length max. m	breadth max. m	depth max. m	free standing	with guide rail fitting
25	8-BER	TOS-8BER	1	0,75	3	2850	direct	3,0	2,0	4,0	28,0	23,0
32	15-BER	TOS-15BER	2	1,5	3	2850	direct	4,0	3,5	4,0	43,0	34,0
50	22-BER	TOS-22BER	3	2,2	3	1450	direct	5,0	5,0	4,5	75,0	61,0
50	37-BER	TOS-37BER	4	3,7	3	1450	direct	6,0	6,0	5,0	91,0	77,0
50	55-BER	TOS-55BER	5	5,5	3	1450	direct	7,0	7,0	6,0	149,0	132,0

This submersible aerator is composed of a B-type pump and an ejector (suction mechanism) so that both agitation and aeration can be carried out simultaneously. The BER aerator features extremely high oxygen dissolution efficiency and a non clog shaver mechanism.




ø Air inlet		25mm,32mm,50mm	
Pumping Fluid	Temperature		0-40°C
	Type of Fluid		Municipal sewage, sewage of food industry
Pump	Compo- nents	Impeller	Non-clog impeller
		Shaft Seal	Double mechanical seal
		Bearings	Shielded ball bearings
	Material	Impeller	Grey iron casting EN-GJL-200
		Casing	Grey iron casting EN-GJL-200
		Suction Plate	Grey iron casting EN-GJL-200
		Diffuser	Construction steel DIN1.0040 nylon coated
		Shaft Seal	Silicon carbide in oil bath
Motor	Type, Poles		Induction motor, 2 poles,Induction motor, 4 poles
	Lubrication		Turbine oil (ISO VG32)
	Insulation		Insulation class E,Insulation class F
	Motor Protector (built-in)		Circle thermal cut-out
	Phase / Voltage		3-phase / 400V / 50Hz / d.o.l.
	Material	Casing	Grey iron casting EN-GJL-150
		Shaft	Stainless steel EN-X6Cr13,Stainless steel EN-X30Cr13
		Cable	Rubber, 10m H07RN-F
Air pipe connection			Inside thread, flange



Dimensions in mm:

Model	A	A1	A2	D	D1	D2	H	H1	H2
8-BER	674	377	297	194	150	180	464	195	150
15-BER	895	537	358	222	150	180	562	224	159
22-BER	1158	687	471	317	220	260	679	312	232
37-BER	1158	687	471	317	220	260	753	312	232
55-BER	1415	861	554	391	220	260	942	341	256

Please mind: discharge bend, duck foot bend and stand set are accessories and must be ordered separately





Contributing to World-wide Prosperity and
Understanding through Worker- and
Environment-friendly Production.

Designed for increased productivity through fully integrated streamlined production systems, Tsurumi's factory in Kyoto (Japan) features a production capacity of a full 1 million pumps per year. Large-scale modern R&D facilities offer optimum conditions for experimenting and testing of even super-large pumps and for developing new products to expand the possibilities and applications of pumps. To provide optimum conditions for our main asset, our workers, as well as for the environment, special emphasis is placed on optimized working conditions with airconditioning, minimized dust and exhaust gas emission, comprehensive recycling and waste recovery.

Tsurumi (Europe) GmbH

Heltorfer Straße 14
D-40472 Düsseldorf
Tel.: +49 (0)211-4179373
Fax: +49 (0)211-4791429
Email: sales@tsurumi-europe.com
www.tsurumi-europe.com

We reserve the right to change specifications and designs herein for improvement without prior notice. Our pumps are for professional use only. In the event that Tsurumi (Europe) GmbH have, in exceptional cases taken over, a manufacturer's warranty, this entitles the enduser to assert remedy free of charge against Tsurumi (Europe) GmbH due to any defect to the product occurring during the guarantee period (see below), also then when the warranty claims against the seller do not or no longer exist. In the event of malfunction, which is attributable to the improper handling by the enduser, no guarantee claim shall arise. Further claims shall not result from the warranty, unless if something to the contrary has explicitly been determined. The decision as to whether remedy is effected by way of replacement or repair shall be at the choice of Tsurumi (Europe) GmbH. The claims shall be time barred after a period of three months after expiry of the guarantee period, however, not before expiry of the warranty period which is valid towards the seller. In the event of doubt, the warranty period shall correspond with the warranty period which is valid between the end-user and his seller.

