



Data sheet 50U2.4



CWL: Continuous running water level
LWL: Lowest running water level



Specification

Electric submersible pump
Degree of protection IP 68
Depth of submersion max. 20 m
Type of impeller Vortex impeller
Free passage 35 mm
Suitable for:
waste water and liquid carrying

Electric motor

Dry-type submersible induction motor
Insulation class E 2Poles 2874 1/min
Starting mode Directly
Rated voltage 400 V 50 Hz 3~
Power uptake 0.53 kW
Rated power 0.40 kW
Rated current 1.1 A
Start current 5.3 A

Cable

10m H07RN-F 4Cx1,5mm²

Motor Protection

Circle thermal protector
(snap-action bi-metal device)

Shaft seal

Double inside mechanical seal in oil bath
additional lubrication by oil lifting device
Primary seal
Silicon carbide on ceramic
Secondary seal
Ceramic on carbon

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller	FC200 (EN-GJL-200)
Pump casing	FC200 (EN-GJL-200)
Motor Frame	FC150 (EN-GJL-150)
Shaft	Stainless steel SUS403

Discharge size

2" (50mm) screwed-in mating flange


Weight

19.2 kg (dry weight of the pump only without cable)

Performance curve



50U2.4

Discharge port	2"
Head	11.0 m
Flow	4.5 l/s
Rated power	0.40 kW
Power input	0.53 kW
Phases	3~
Voltages	400 V
Frequency	50 Hz
Rated current	1.1 A
Starting current	5.30 A
Number of poles	2
Speed	2874 1/min
Starting mode	Directly
Insulation class	E



Dimensions

50U2.4



50U2.4


CWL: Continuous running water level
LWL: Lowest running water level



Tsurumi Europe GmbH
24.08.2011

Heltorfer Str. 14 * 40472 Düsseldorf * Germany
Tel.: +49-211-4179373 sales@tsurumi.eu
Fax: +49-211-4791429 www.tsurumi.eu

Sectional drawing 50U2.4



50U2.4-52

No.	Denomination	Remark	No.	Denomination	Remark
1	Cable	H07RN-F	55	Rotor	.
20	Pump casing	FC200 (EN-GJL-200)	56	Stator	.
21	Impeller	FC200 (EN-GJL-200)	64	Motor Frame	FC150 (EN-GJL-150)
25	Mechanical seal	W-14H	68	Handle	Synthetic resin
26	Oil seal	SC-15287	71	Shaft protection sleeve	Stainless steel SUS 1.4016
29	Oil casing	FC150 (EN-GJL-150)			
32	Coupling Set &	Synthetic resin			
35	Oil screw	Stainless steel SUS304			
36	Lubricant	Turbine oil (ISO VG32)			
48	Screwed Flange	FC200 (EN-GJL-200)			
50	Motor cover	FC150 (EN-GJL-150)			
51	Main cover	FC150 (EN-GJL-150)			
52A	Upper bearing	6201ZZC3			
52B	Lower bearing	6202ZZC3			
53	Motor Protector	.			
54	Shaft	Stainless steel SUS403			