

Receiver
From

Society
Reference
Address
Phone
Fax
E-mail

Item n° :

102660000

Model :

JET 62 M

Pump data

Pressure rating : 6 bar (600 kPa)
Min. fluid temperature : 0 °C
Max. fluid temperature : 35 °C
Max. Temperature operating : 40 °C

Priming capacity :

H m	2	3	4	5	6	7	8	9
Q m³/h	2.46	2.28	2.04	1.86	1.62	1.32	1.14	0.78

Requested data



Flow : 0.00 m³/h
Head : 0.00 m
Fluid : Water, pure
Fluid Temperature : 20 °C
Density : 998.3 kg/m³
Kinematic viscosity : 1.005 mm²/s
Vapor pressure : 100.00 kPa

Hydraulic data (duty point)

Flow :
Head :

Materials

Pump body	Cast iron 200 UNI ISO 185
Support	Die cast aluminium
Impeller	Technopolymer A
Mechanical seal	Carbon/Ceramic
OR ring	NBR Rubber
Shaft with rotor	AISI 416 X12 CrS 13 UNI 6900/71
Diffuser	Technopolymer A

Curve tolerance according to ISO 9906

Motor data

Motor brand :	DAB
Nominal power P2:	0.44 kW
Rated speed :	2850 rpm
Rated voltage :	1~ 220-240 V 50 Hz
Nominal current :	3.12 A
Degree of protection :	IP 44

Dimensions in
mm

A	395	DNA	1" G	G	111
A1	390	DNM	1" G	H	193
B	178	E	192	H3	144
C	108	F	14	I	9

Weight : 10.5 kg


Pump connection

Suction side	1 " G / 6 bar (600 kPa)
Discharge side	1 " G / 6 bar (600 kPa)

Receiver	From
Society Reference Address Phone Fax E-mail	

JET 62 M

Curve tolerance according to ISO 9906



Hydraulic data (duty point)


Suction side 1 " G 6 bar (600 kPa)	Discharge side 1 " G 6 bar (600 kPa)	Flow : 0 m³/h	Head : 0 m	Rated speed : 2850 rpm
Project	Project ID	Created by	Created on 22/08/2014	

Receiver

From

Society
Reference
Address
Phone
Fax
E-mail

JET 62 M



Dimensions in mm

1	A	395	H3	144		
2	A1	390	I	9		
3	B	178				
4	C	108				
5	DNA	1" G				
6	DNM	1" G				
7	E	192				
8	F	14				
9	G	111				
10	H	193				

Pump connection

Suction
1" G
6 bar (600 kPa)

Discharge
1" G
6 bar (600 kPa)

Project

Project ID

Created by

Created on

22/08/2014