



Data Sheet LH619-50



Classification

Electric submersible pump
Protection class IP68
Depth of submersion max. 100m
Closed type impeller
Max. solid handling 12mm
Suitable for rain water, ground water, sand carrying water

Electric Motor

Dry-type submersible induction motor,
Insulation class B, 2 poles, 2850 r.p.m.
Direct on line start
Voltage: 400V, 50Hz, 3-phase
Power input: 21,9kW
Power output: 19,0kW
Nominal current: 34,0A
Start current: 249,0A

Electric Cable

20m 4Cx14mm²

Motor Protection

Circle thermal protector
(snap-action bi-metal device)

Shaft Seal

Double mechanical seal in oil bath
additional lubrication by oil lifting device
Primary Seal:
silicon carbide on silicon carbide
Secondary Seal:
silicon carbide on carbon

Bearings

Shielded ball bearings, maintenance-free

Materials

Impeller:	Chromium iron casting
Casing:	FC200 (EN-GJL-200)
Mouth ring:	Chromium iron casting
Motor frame:	FC200 (EN-GJL-200)
Shaft:	SUS420J2 (EN-X30Cr13)


Discharge Connection

6" (150mm) JIS 10K flange

Weight


275 kg (dry weight of the pump without cable)

Dimensional Drawing LH619-50



LH619-50

Sectional Drawing LH619-50




LH619-50

No.	Description	Qty.	Remarks	No.	Description	Qty.	Remarks
1	Cabtyre Cable	1	20m 4Cx14mm2	37	Discharge Pipe	1	SS400 (DIN 1.0040)/Carbon Steel SGP
6	Stuffing Box	1	FC200 (EN-GJL-200)	43	Cathodic Protection Plate	3	Aluminium Alloy ALAP
20	Pump Casing	1	FC200 (EN-GJL-200)	50	Motor Bracket	1	FC200 (EN-GJL-200)
21	Impeller	1	Chromium Iron Casting HiCrFC	51	Head Cover	1	FC200 (EN-GJL-200)
22	Suction Cover	1	FC200 (EN-GJL-200)	52A	Upper Bearing	1	6307ZZC3
23	Strainer Stand	1	SS400 (DIN 1.0040)	52B	Lower Bearing	1	6311ZZD2C3
25	Mechanical Seal	1	HT-3540	53	Motor Protector	1	
26A	Oil Seal	1	SC40588	54	Shaft	1	SUS420J2 (EN-X30Cr13)
26B	Oil Seal	1	TC385811	55	Rotor	1	
26C	Oil Seal	1	TCN385811	56	Stator	1	
26D	Labyrinth Ring	1	SUS403 (EN-X6Cr13)	60	Bearing Housing	1	FC200 (EN-GJL-200)
29	Oil casing	1	FC200 (EN-GJL-200)	64	Motor Frame	1	FC200 (EN-GJL-200)
34A	Suction Mouth	1	FC200 (EN-GJL-200)	65	Outer Cover	1	SS400 (DIN 1.0040)
34B	Mouth Ring	1	Chromium Iron Casting HiCrFC	71A	Upper Shaft Sleeve	1	SUS403 (EN-X6Cr13)
35	Oil Plug	2	SUS304 (EN-X5CrNi18-10)	71B	Lower Shaft Sleeve	1	SUS403 (EN-X6Cr13)
36	Lubricant	1	Turbine Oil (ISO VG32)	72	Eyebolt	2	SS400 (DIN 1.0040)

Pump Performance Curve

LH619-50

Discharge Bore	150 mm
Total Head	30,0 m
Capacity	2,0 m ³ /min
Motor Output	19,0 kW
Motor Input	21,9 kW
Phase	3
Voltage	400 V
Frequency	50 Hz
Rated Current	34,0 A
Starting Current	249,0 A
Poles	2
Revolution	S.S. 2850 r.p.m.
Starting Method	direct on line
Insulation Class	B



LH619-50 (A-04070-1)